

HD-L20UH

Professional PTZ Camera



업계에서 가장 다재 다능한 전문가 급 PTZ 카메라 인 HD-L20UH에는 USB, HDMI, SDI 및 IP 연결이 포함되어있어 일반 강의 및 회의 캡처, PC 기반 웹 회의, UC 응용 프로그램, 화상 회의, 원격 교육, 텔레프레즌스, 감시, 원격 관리, IT 제어 등에 널리 사용됩니다.

20배의 광학줌과 3.5백만 화소의 동급최강의 우수한 성능을 통해 강의 저장장치와 연동하여 최적의 강의녹화 시스템 구축도 가능합니다.

최고 성능의 비디오

- + Full HD video quality with 1080p@60
- + 20x optical zoom

듀얼 IP 스트림

- + H.264 and MJPEG compression enabling Full HD video stream by ultra low bandwidth over RTSP, TCP/IP, HTTP, etc
- + RTMP, RTSP, TCP/IP, HTTP streaming

저조도

- + High video quality in low light conditions

깨끗한 화질

- + Super-high SNR
- + Advanced 2D and 3D noise reduction
- + White balance-Auto, Manual, One-push

풍부한 출력지원

- + HDMI, HD-SDI, USB, IP
- + UVC control optional
- + POE power supply optional

유연한 제어환경

- + RS-232 (daisy-chainable)
- + RS-422 & RS-485
- + UVC PTZ control
- + 255 presets

다양한 호환성

- + Bee3 Plus
- + LC-390R & LC-390S
- + Cam-Motion
- + AMX, Crestron, etc

Huddle Spaces

Executive Offices

Meeting Rooms

Conference Rooms

Boardrooms

Classrooms

Auditorium

Professional PTZ Camera

HD-L20UH



Functional Specifications

Item No.	HD-L20UH
Image Sensor	1/2.8" Progressive CMOS
Effective Pixels	3.50 Megapixels
Resolution HD	1080p60/50,1080i60/50,1080p30/25, 720p60/50
Signal System	PAL/NTSC
Lens	20X optical zoom f=4.7mm(w)~94.0 mm(f) F1.6~F2.8
Horizontal View Angle	58.7°(W)~3.2°(T)
Pan	355°(max. speed:80°/s)
Tilt	-30° to +90° (max. speed: 60°/s)
Focus System	Auto/Manual
S/N Ratio	≥50db
Preset Position	9 preset positions by IR remote controller, 255 preset positions by Keyboard
Minimum Illumination	0.1Lux
Exposure Control	Auto/Manual/Priority AE/Exposure Compensation/ Bright
Shutter Speed	1/1~1/10,000s
Gain	Auto/Manual

Item No.	HD-L20UH
White Balance	Auto/ Indoor/Outdoor/Manual
Image Effect	Full color/Black & white/Electronic flip
Video Output HD	HDMI, 3G/HD-SDI, USB, IP
Encoding	H.265/H.264/M-JPEG Dual IP-Stream Out
Other Input	Audio Line In
Control Protocol	VISCA, PELCO P/D
Control Mode	RS-232C, RS-422/485
Power	12V DC(10.8~13.0V DC)
Power Consumption	Max. 30W(DC 12V)
Storage Temperature	-20-60°C
Dimensions	(L)170 ×(W)150 ×(H)190mm
Weight	1550g
Color	White / Black
Accessories	DC 12V power adapter, IR Remote, Operation manual, RS-232C Cable, DVI adapter, HDMI cable, USB cable, Ceiling bracket